

INJ-IX01-PB & INJ-IX01-2PB

- ◀ 1x port Industrial 10M/100M/1G/2.5G/5G/10G IEEE802.3af/at/bt PoE type 4 Injector (90W/port)
- ▶ 2x port Industrial 10M/100M/1G/2.5G/5G/10G IEEE802.3af/at/bt PoE type 4 Injector (180W, 90W/port)

NEW



- PoE power budget maximum 90W/port
- Compliant with 10/100/1G/2.5G/5G/10GBase-T(X) & IEEE802.3af/at/bt type 4 PoE
- Railway EN50121-4, Heavy industrial EN61000-6-2, EN61000-6-4, CE, FCC certified



INJ-IX01-PB and INJ-IX01-2PB are an industrial grade, 1/2x port 10M/100M/1G/2.5G/5G/10G Ethernet PoE (Power over Ethernet) injector. PoE describes a system to pass electrical power safely, along with data, on Ethernet cabling. The original IEEE802.3af/at/bt PoE standard provides up to 90W of DC power to each device. Housed in a rugged DIN rail or wall mountable enclosure, this product is designed for harsh environments, such as industrial networking, security, intelligent transportation systems (ITS) and is also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications. Standard operating temperature range models (-10 to 60°C) and wide operating temperature range models (-40 to 75°C) fulfill the special needs of industrial automation applications.

Features

- Provides 1x port IEEE 802.3at/af/bt type 4 PoE Injector (INJ-IX01-PB)
- Provides 2x port IEEE 802.3at/af/bt type 4 PoE Injector (INJ-IX01-2PB)
- Wide operating temperature -40 ~ 75°C
- IP30 rugged metal housing and fanless


Specifications

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3bz 2.5GBase-T, 5GBase-T IEEE 802.3an 10GBase-T
PoE Standard	IEEE802.3bt, IEEE 802.3at, IEEE802.3af
PoE & RJ-45 Pin Assignment	Provides 2/4 pairs PoE Positive (V+): RJ-45 pin 1, 2, 4, 5 Negative (V-): RJ-45 pin 3, 6, 7, 8 Ethernet Data (1, 2, 3, 6, 4, 5, 7, 8)
Network Connector	Per port provide 1 RJ-45 for Ethernet data, and 1 RJ-45 for Ethernet data with PoE Output power
Network Cable	Supports 100 meter for below cable, please see Figure: Above Cat.5e UTP/STP cable for 10/100/1G/2.5GBase-T Above Cat.6 UTP/STP cable for 5GBase-T Above Cat.6A UTP/STP cable for 10GBase-T
LED	Per unit: PWR1, PWR2 (Green) for Power status PoE (Green) per port ON : PoE on OFF: PoE off
Reverse Polarity Protection	Supported for power input
Overload Current Protection	Supported
Power Supply	Redundant Dual 48V (44~57VDC) Input Power (Removable Terminal Block) 54~57VDC VDC for 90W (4 Pairs) PoE application 52~57VDC for 60W (4 Pairs) PoE application 52~57VDC for 30W (2 Pairs) PoE application 44~57VDC for 15.4W (2 Pairs) PoE application
PoE Power Budget	90W/port ,total 90W (INJ-IX01-PB) 90W/port ,total 180W (INJ-IX01-2PB)
Power Consumption	TBD
Removable Terminal Block	Provides 4 Pin for redundant power 1 and Power 2 input connection
Operating Temperature	-10 ~ 60°C (INJ-IX01-PB, INJ-IX01-2PB) -40 ~ 75°C (INJ-IX01-PBE, INJ-IX01-2PBE)
Operating Humidity	5% to 95% (Non-condensing)

Storage Temperature	-40 ~ 85°C
Housing	Rugged Metal, IP30 Protection and fanless
Dimensions	106x 38.6 x 152 mm (D x W x H)
Weight	TBD
Installation Mounting	DIN Rail mounting, and Wall Mounting (Optional)
MTBF	TBD (MIL-HDBK-217)
Warranty	5 years
Certification	
EMC	CE (EN55032, EN55035)
EMI	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4
Immunity for Heavy Industrial environment	EN 61000-6-2
Emission for Heavy industrial environment	EN 61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (EFT) Level 3, Criteria A EN 61000-4-5 (Surge) Level 3, Criteria B EN 61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF) Field strength 300A/m Criteria A
Safety	EN62368-1 (Pending)
Surge Protection Shock	4KV for PoE and UTP IEC 60068-2-27
Freefall	IEC 60068-2-31
Vibration	IEC 60068-2-6


Application

Figure : INJ-IX01-PB Ethernet PoE Injector




Dimensions

INJ-IX01-PB



INJ-IX01-2PB



Ordering Information

Model Name	Ethernet port	Ethernet with PoE port		Power Input	Certification			Operating Temperature
	10/100/1G/2.5G/5G/10G Base-T(X)	IEEE802.3af/at/bt (PSE)	Power Budget	Redundant	EN50121-4	EN61000-6-2 EN61000-6-4	CE/FCC	
INJ-IX01-PB	1	1	90W	48VDC	V	V	V	-10~60°C
INJ-IX01-PBE	1	1	90W	48VDC	V	V	V	-40~75°C
INJ-IX01-2PB	2	2	180W (90W/port)	48VDC	V	V	V	-10~60°C
INJ-IX01-2PBE	2	2	180W (90W/port)	48VDC	V	V	V	-40~75°C

Package List

- PoE injector device
- Terminal block
- Din Rail with screws

Optional Accessories

Wall Mount Kit

IND-WMK05	Wall Mount kit for Industrial product (2pcs in 1 set, 42x30mm)
-----------	--

Industrial Power Supply

NDR-240-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 240W, -20 ~ +70°C (For INJ-IX01-2PB)
NDR-120-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 120W, -20 ~ +70°C (For INJ-IX01-PB)