

## db PROXLOCK

### 125 KHz proximity card authentication

db ProxLock authenticates industry-standard 125 kHz proximity cards for access control. Use the cards that currently authenticate for building/room access, extending their function to server cabinets.

## KEY PRODUCT FEATURES

- Works with both db Bus and db Sentry controllers
- Simple integration with any 3<sup>rd</sup>-party ACM solution
- Unlimited number of users
- For use with low-frequency proximity cards
- Compatible with server cabinets from most major manufacturers
- Cost-effective & easy to implement
- Anti-counterfeiting features and enhanced encryption capability



## TECHNICAL SPECIFICATIONS

### DIMENSIONS:

- Height: 213 mm
- Width: 37 mm
- Depth: 24.5 mm

### COMMUNICATION PROTOCOLS

- Digitus control equipment
  - RS232
- 3<sup>rd</sup>-party Access Panel
  - Wiegand

### STATUS MONITORING:

- Built-in optical sensor to monitor handle position

### OVERRIDE:

- Optional mechanical key (custom key cylinders available)

### USE WITH:

- Digitus control equipment
  - db Bus
  - db Sentry
- 3<sup>rd</sup>-party Access Panels (via Wiegand)

### CARD FORMATS:

- 26 bit Wiegand (H10301)
- 37 bit (H10302)
- 37 bit (H10304)
- 35 bit Corporate 1000

### LED:

- Red and Blue

### CABINET PANEL PREP

- 25mm x 150mm

### QUICK DISCONNECT:

- Allows door to be easily removed without rerouting cables