

LTPM16

Outdoor Pan and Tilt Unit for Loads up to 12 kg (26.5 lb)

IP66, maximum load of 12 kg (26.5 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM16
(Movement in Vertical Plane)	
Accuracy	±0.1°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D
Baud Rate	9,600 bps
Standard Setting	Available with BNC or network cable (selectable)
OSD menu	Available
Preset	Up to 254
Position Query	Support
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	197 mm × 266 mm × 167 mm (7.8 in × 10.5 in × 6.6 in)
Weight	7.5 kg (16.5 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 12 kg (26.5 lb)
- High-precision worm gear, self-locking for strong wind resistance when power off
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V DC
- Support analogue or network cameras (optional)

Tech Specs

Model	LTPM16
Maximum Load	12 kg (26.5 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V DC
Power Consumption	50 W maximum
Pan Speed	0.2° to 30° per second
Tilt Speed	0.2° to 15° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Range	-60° to 15°