

# LTSU10

## IP66 High Speed Pan and Tilt System



Model	LTSU10
Area (Ø)	• 75 mm (3.0 in)
Internal Usable Size (W × H × L)	83 mm × 83 mm × 170 mm (3.3 in × 3.3 in × 6.7 in)
Dimensions (W × H × L)	425 mm × 206 mm × 208 mm (16.7 in × 8.1 in × 8.2 in)
Weight	8.8 kg (19.4 lb)
Illumination Source	-
Wavelength	-
Illumination Distance	-
Beam angle	-
Illumination Power Consumption	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-6P enclosure rating
- Pan and tilt speed adjustable
- Wiper included

### Tech Specs

Model	LTSU10
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V DC
Power Consumption	50 W
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	0.1° to 120° per second adjustable
Tilt Range (Movement in Vertical Plane)	-90° to 90°
Tilt Speed	0.1° to 90° per second adjustable
Accuracy	± 0.1°
Preset	254
Relative Humidity	5 % to 95 % noncondensing
Operating Ambient Temperature	-35 °C to 55 °C (-31 °F to 131 °F)
Communication Protocols	RS-485, Manchester
Baud Rate	Pelco-D
Window Viewing	9,600 bps
	• 57 mm (2.2 in) (with wiper)