

LTAK12

Control Panel



Model	LTAK12
Power Consumption	• 0.6 W maximum (LTAK12, LTAK12-R) • 0.5 W maximum (LTAK12-U)
Dimensions (W × H × L)	158 mm × 107 mm × 150 mm (6.2 in × 4.2 in × 5.9 in)
Weight	0.5 kg (1.1 lb)

*Design and specifications are subject to change without prior notice.

Features

- RS-485/USB 2.0/RJ-45 (optional)
- Joystick for accurate control
- LCD Display

Available Models

Model	Communication
LTAK12	RS-485
LTAK12-U	USB
LTAK12-R	RJ-45

Tech Specs

Model	LTAK12
Joystick	4D
Control Address	0 to 255
Operating Ambient Temperature	0 °C to 50 °C (32 °F to 131 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	• RS-485 (LTAK12) • USB 2.0 (LTAK12-U) • RJ-45 (LTAK12-R)
Communication Baud Rate	1,200 bps, 2,400 bps, 4,800 bps, 9,600 bps (LTAK12)
Protocols	• Pelco-D, Pelco-P, Dahua, Hik (LTAK12) • Hid (LTAK12-U) • ONVIF (LTAK12-R)
Input Power	• 12 V DC (LTAK12, LTAK12-R) • 5 V DC (LTAK12-U)