

LTPM18

Military-grade Pan and Tilt Unit for Loads up to 120 kg (264.5 lb)

IP66, maximum load of 120 kg (264.5 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM18
Vertical Plane)	
Power	300 W maximum
Consumption	
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-422/RS-485 (optional)
Protocols	Pelco-D
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	• Available with network cable (100Mbps) • Available with BNC cable (optional)
OSD menu	-
Preset	200
Dimensions (W × H × L)	337 mm × 469 mm × 264 mm (13.3 in × 18.5 in × 10.4 in)
Weight	50 kg (110.2 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 120 kg (264.5 lb)
- Aluminum alloy construction
- Designed for harsh environment applications
- Pan and tilt speed adjustable
- Support network or analogue cameras (optional)
- Input power: 48 V DC

Tech Specs

Model	LTPM18
Maximum Load	120 kg (264.5 lb)
Type	Harsh environment applications, top load, worm gear
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	48 V DC
Power protection	TVS 8000V lightn -proof, surge proof, in line with GB/T17626.5 Level 4
Accuracy	± 0.1°
Pan Speed	0.1° to 15° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	0.1° to 7° per second
Tilt Range (Movement in	-45° to 45°