

## LTPM05

### Outdoor Pan and Tilt Unit for Loads up to 15 kg (33.1 lb)

IP66, maximum load of 15 kg (33.1 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM05
Horizontal Plane)	
Tilt Speed	0.01° to 30° per second
Tilt Range	-75° to 40° (-90° to 40° optional)
(Movement in Vertical Plane)	
Accuracy	0.225° ± 0.003°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Auto Scan	Up to 5 lines, based on OSD function, configurable speed
Auto Cruise	Up to 8 groups, based on OSD function, configurable speed
Continuous Scan	8 line, configurable speed and angles
Angles Display	Support
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	<ul style="list-style-type: none"> <li>Available with BNC Cable (LTPM05-A)</li> <li>Available with network cable (100Mbps) (LTPM05-N)</li> </ul>
OSD menu	Available
Preset	Up to 80
Lens Driven	10 V/6 V software control and adaptive
Lens Interface	Support (pan and tilt preset configuration interface)
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	249 mm × 230 mm × 302 mm (9.80 in × 9.06 in × 11.89 in)
Weight	13 kg (28.66 lb)
Note	-

\*Design and specifications are subject to change without prior notice.

## Features

- IP66, NEMA-6P enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

## Available Models

Model	Support
LTPM05-A	Analogue
LTPM05-N	Network

## Tech Specs

Model	LTPM05
Maximum Load	15 kg (33.1 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V AC ± 25 %
Power Consumption	max. 85 W (heater off), max. 95 W (heater on)
Pan Speed	0.01° to 60° per second
Pan Range	0° to 360° continuous
(Movement in	