

LTPM06

Outdoor Pan and Tilt Unit for Loads up to 50 kg (110.2 lb)

IP66, maximum load of 50 kg (110.2 lb), speed adjustable pan and tilt, aluminum alloy construction



Features

- IP66, NEMA-6P enclosure rating
- Maximum load 50 kg (110.2 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)
- Input power: 24 V AC/24 V DC (available)

Available Models

Model	Support	Input Power
LTPM06-A-2	Analogue	24 V AC
LTPM06-A-6	Analogue	24 V DC
LTPM06-N-2	Network	24 V AC
LTPM06-N-6	Network	24 V DC

Tech Specs

Model	LTPM06
Maximum Load	50 kg (110.2 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	• 24 V AC (LTPM06-A-2, LTPM06-N-2) • 24 V DC (LTPM06-A-6, LTPM06-N-6)

Model	LTPM06
Power Consumption	85 W
Pan Speed	0.01° to 30° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	0.01° to 15° per second
Tilt Range (Movement in Vertical Plane)	• -45° to 45° for load 50 kg (110.2 lb) (factory setting) • -60° to 60° for load 40 kg (88.2 lb) • -80° to 80° for load 26 kg (57.3 lb) • -90° to 90° for double load
Accuracy	0.225° ± 0.003°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Auto Scan	Up to 8 lines, based on OSD function, configurable speed
Auto Cruise	Up to 8 groups, based on OSD function, configurable speed
Keep Watch	Programmed a preset, an auto scan line or an auto cruise group, based on OSD function, dwell time counting down display
Helix Scan	8 line, configurable speed and angles
Continuous Scan	8 line, configurable speed and angles
Angles Display	Real-time on screen display/Response by query command
Communication	RS-485, RS-422
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	• Available with BNC Cable (LTPM06-A-2, LTPM06-A-6) • Available with network cable (100Mbps) (LTPM06-N-2, LTPM06-N-6)
OSD menu	Available
Preset	Up to 80
Lens Driven	10 V/6 V software control and adaptive
Lens Interface	Support (pan and tilt preset configuration interface)
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	340 mm × 206 mm × 390 mm (13.4 in × 8.1 in × 15.6 in)
Weight	20 kg (44.1 lb)
Note	-

*Design and specifications are subject to change without prior notice.