

LTSU05

Outdoor Pan and Tilt Unit



Model	LTSU05
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable Size (W × L × H)	-
Dimensions (W × L × H)	223 mm × 333 mm × 513 mm (8.8 in × 13.1 in ×20.2 in)
Weight	25 kg (55.1 lb)
Wavelength	-
Illumination Distance	-
Beam angle	-

*Design and specifications are subject to change without prior notice.

Features

- IP67, NEMA-6P enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper included
- Support analogue or network cameras (optional)

Tech Specs

Model	LTSU05
Type	Indoor/Outdoor
Protection Rating	IP67, NEMA-6P enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	220 V AC
Power Consumption	60 W (heater: 25 W), standby max. 15 W
Pan Speed	0.1° to 100° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	0.1° to 100° per second
Tilt Range (Movement in Vertical Plane)	-90° to 40°
Accuracy	0.02°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication Protocols	RS-485 Pelco-D, Pelco-P